

JMLU2.MH25918 **Gaskets and Seals - Component**

Page Bottom

Gaskets and Seals - Component

See General Information for Gaskets and Seals - Component

POLY TEC SRL MH25918

Strada Panealba 4 10040 Volvera, To ITALY

Cellular Material

Compound Dsg.	Max Svc Temp (°C)	Min Svc Temp (°C)	Density (pcf)	Tensile Str (psi)	Elong (%)	Max Comp Set (%)	End Use
Two part poured-in-place open cell Polyurethane supplied as two liquid components							
Polytix 30.11	80	-20	-	25	100	-	1

The final acceptance of a gasket material in a specific end-use application is dependent on its installation and use, and may require additional evaluation with respect to ingress or leakage of solids (such as dusts), liquids or gases, or other features dependent on the design and construction of the equipment in which it is used.

1 - Suitable for use in UL 50 and UL 50E (continuous compression) applications.

Marking: Company name, compound designation and the Recognized Component Mark, on the material, on a substantial tag, on the container or the smallest packaging.

Last Updated on 2017-08-18

Questions? Print this page Terms of Use Page Top

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a nonmisleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".